
SupIR 40mm f/1.0, Manual Focus 680395*





HFOV	320x240	384x288	640x480	1024x768
17µ	7.8°	9.3°	15.3°	
12µ	5.5°	6.6°	10.9°	17.2°

Property			Value	Value				
Optical								
Focal Length			40mm	40mm				
F#			1.0	1.0				
Average transmission (8-12µm)			94% (HD)	94% (HD) / 87% (HC)				
Back Focal Length			17.8mm ir	17.8mm in air				
Mechanical								
Focus Mechanism			Manual	Manual				
Depth of Field			100m to ir	100m to infinity				
Focus Range			3m to infin	3m to infinity				
Weight			144gr	144gr				
Max. Dimensions			Ø61mm x	Ø61mm x 49mm				
Environmental								
Operation Temperature			-40°C to +	-40°C to +80°C				
Storage Temperature			-50°C to +	-50°C to +85°C				
Sealing		IP 67 front	IP 67 front element only					
Configurations	Weight (gr)	Dimensions	BWD**	Thread	Coating			
680395-001	- 144	Ø61mm x 49mm	12.15	M48x0.75	HD			
680395-002			12.10		HC			

HD FORMAT

* Requires export license

* The ICD drawing provided here is primarily a representation and may not accurately reflect the product's actual dimensions and specifications. For precise integration specifications contact your local sales representative.

** The BWD value is calculated for a unique detector setup with varying sealing windows in terms of thickness and material. For more details, contact your local sales representative.

